

Product Name: Hansaflex Öl HVLPD 46
Revision: 01.07.2025

Sicherheitsdatenblatt EN

gemäß Verordnung (EG) Nr. 1907/2006

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Hansaflex Öl HVLPD 46

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Hydraulic fluids

Uses advised against

none

1.3. Details of the supplier of the safety data sheet

Company name: HANSA-FLEX AG
Street: Zum Panrepel 44
Place: D-28307 Bremen
Telephone: +49 (0) 421 48907 0
Responsible Department: info@hansa-flex.com

1.4. Emergency telephone number:

Gift-Informationszentrum Nord (Göttingen) - Telefon 0551-19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is not classified as hazardous in accordance with Regulation (EC) No 1272/2008.

2.2. Label elements

Regulation (EC) No 1272/2008

Special labelling of certain mixtures

EUH210 Safety data sheet available on request.

2.3. Other hazards

This mixture contains no substances of very high concern (SVHC) (>0,1%) which are included in the Candidate List according to Article 59 of REACH.

For information or further instructions, see also section 11 or 12.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified			15 - < 20 %
	265-159-2	649-469-00-9	01-2119480132-48	
	Asp. Tox. 1; H304			
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified			1 - < 3 %
	265-158-7	649-468-00-3	01-2119487077-29	
	Asp. Tox. 1; H304			

Full text of H and EUH statements: see section 16.

Product Name: Hansaflex Öl HVLPD 46
Revision: 01.07.2025

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-56-9	265-159-2	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified	15 - < 20 %
		inhalation: LC50 = >5,53 mg/l (dusts or mists); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg	
64742-55-8	265-158-7	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified	1 - < 3 %
		inhalation: LC50 = > 5,53 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	

Further Information

Note L: The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method" Institute of Petroleum, London).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Never give anything by mouth to an unconscious person or a person with cramps. When in doubt or if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

If swallowed or in the event of vomiting, risk of entering the lungs.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Sand. Foam. Carbon dioxide (CO₂). Extinguishing powder. In case of major fire and large quantities: Water spray jet. Water mist.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

In case of fire may be liberated: Carbon monoxide (CO). Carbon dioxide (CO₂) Sulphur dioxide (SO₂) Nitrogen oxides (NO_x)

5.3. Advice for firefighters

Product Name: Hansaflex Öl HVLPD 46
Revision: 01.07.2025

In case of fire and/or explosion do not breathe fumes. In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ventilate affected area.
Special danger of slipping by leaking/spilling product.

For non-emergency personnel

Wear personal protection equipment (refer to section 8).

For emergency responders

No special measures are necessary.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Treat the recovered material as prescribed in the section on waste disposal.
Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

No information available.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Wear suitable protective clothing. (See section 8.)
Avoid formation of oil dust.

Advice on protection against fire and explosion

Usual measures for fire prevention. Keep away from sources of ignition - No smoking.
Fire class B

Advice on general occupational hygiene

Clean skin thoroughly after working.
Do not put any product-impregnated cleaning rags into your trouser pockets.

Further information on handling

Do not breathe vapour/aerosol.
Avoid contact with eyes and skin.
General protection and hygiene measures: See section 8.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Only use containers specifically approved for the substance/product.

Hints on joint storage

Do not store together with: Gas. Explosives. Oxidizing substances. Radioactive substances. Infectious substances

Product Name: Hansaflex Öl HVLPD 46
Revision: 01.07.2025

Further information on storage conditions

Temperature control required. Protect from light. Keep container tightly closed. Do not allow contact with air.

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Name of agent	Exposure route	Effect	Value
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m ³
Worker DNEL, long-term		inhalation	local	5,58 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	1,19 mg/m ³
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified			
Worker DNEL, long-term		inhalation	systemic	2,73 mg/m ³
Worker DNEL, long-term		inhalation	local	5,58 mg/m ³
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	1,19 mg/m ³

PNEC values

CAS No	Name of agent	Value
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified	
Secondary poisoning		9,33 mg/kg
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified	
Secondary poisoning		9,33 mg/kg

Additional advice on limit values

Air limit values:

Possibility of exposure to Aerosol (Mineral oil)

Limit value (TLV-TWA) = 5 mg/ m³ - Source: ACGIH

Limit value (TLV-STEL) = 10 mg/ m³ - Source: ACGIH

STEL: short-term exposure limits

TLV: Threshold Limiting Value

TWA: time weighted average

ACGIH: American Conference of Governmental Industrial Hygienists

8.2. Exposure controls

Product Name: Hansaflex Öl HVLPD 46
Revision: 01.07.2025



Appropriate engineering controls

Provide adequate ventilation.

Individual protection measures, such as personal protective equipment

Eye/face protection

Safety goggles with side protection. In case of increased risk add protective face shield. EN 166

Hand protection

Use safety gloves of following materials: NBR (nitrile) / neopren / viton (permeationslevel 5 - 6), Cat. II according to norm EN 374/EN 388.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Gloves must be periodically inspected and changed in case of wear, perforations or contaminations.

In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Oil-resistant and hardly inflammable protective clothing.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

-aerosol or mist formation

-Exceeding exposure limit values

Suitable respiratory protection apparatus: Respiratory equipment in case of nebulosity or aerosol: Use a mask with a filter type A2, A2/P2 or ABEK.

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Thermal hazards

Wear protective clothing for operations with hot material: heat resistant coveralls (with trousers legs over boots and sleeves over cuffs of gloves), heat resistant heavy duty antiskid boots (e. g. leather).

Environmental exposure controls

No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	clear
Odour:	characteristic

	Test method
Melting point/freezing point:	No information available.
Boiling point or initial boiling point and boiling range:	No information available.
Flammability:	No information available.
Lower explosion limits:	No information available.
Upper explosion limits:	No information available.
Flash point:	228 °C COC
Auto-ignition temperature:	No information available.

Product Name: Hansaflex Öl HVLPD 46
Revision: 01.07.2025

Decomposition temperature:	No information available.
pH-Value:	No information available.
Viscosity / kinematic: (at 40 °C)	45,89 mm ² /s DIN EN ISO 3104
Water solubility:	Immiscible
Solubility in other solvents	No information available.
Partition coefficient n-octanol/water:	No information available.
Vapour pressure: (at 20 °C)	No information available.
Vapour pressure: (at 50 °C)	No information available.
Density (at 15 °C):	0,8757 g/cm ³ DIN 51757
Bulk density:	No information available.
Relative vapour density:	No information available.
Particle characteristics:	No information available.

9.2. Other information

Information with regard to physical hazard classes

Explosive properties	
none	
Sustained combustibility:	No data available
Self-ignition temperature	
Solid:	No information available.
Gas:	No information available.
Oxidizing properties	
none	

Other safety characteristics

Evaporation rate:	No information available.
Solvent separation test:	No information available.
Solvent content:	No information available.
Solid content:	No information available.
Sublimation point:	No information available.
Softening point:	No information available.
Pour point:	-39 °C ISO 3016
Viscosity / dynamic:	No information available.
Flow time:	No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No hazardous reactions known.
Refer to chapter 10.5.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

Oxidising agent, strong

Product Name: Hansaflex Öl HVLPD 46
Revision: 01.07.2025

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified				
	oral	LD50 >5000 mg/kg	Rat.	ECHA Dossier	
	dermal	LD50 >5000 mg/kg	Rabbit.	ECHA Dossier	
	inhalation (4 h) dust/mist	LC50 >5,53 mg/l	Rat.	ECHA Dossier	
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified				
	oral	LD50 > 5000 mg/kg	Rat	ECHA Dossier	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	ECHA Dossier	OECD Guideline 402
	inhalation (4 h) dust/mist	LC50 > 5,53 mg/l	Rat	ECHA Dossier	OECD Guideline 403

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Product Name: Hansaflex Öl HVLPD 46
Revision: 01.07.2025

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified:

In vitro mutagenicity/genotoxicity:

Method:

-OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)

-OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

-OECD Guideline 471 (Bacterial Reverse Mutation Assay)

Result: = negative

Literature information: REACH Dossier

Chronic dermal toxicity :

Exposure time: ~546 d

Species: Mouse.

Method: OECD Guideline 451

Result: Carcinogenicity = negative

Literature information: REACH Dossier

Reproductive toxicity: :

Exposure route: oral.

Species: Rat.

Method: OECD Guideline 421

Result: NOAEL >1000 mg/kg

Literature information: REACH Dossier

Developmental toxicity/teratogenicity :

Exposure route: dermal.

Species: Rat.

Method: OECD Guideline 414

Result: NOAEL >2000 mg/kg

Literature information: REACH Dossier

Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified:

In vitro mutagenicity/genotoxicity:

Method: OECD Guideline 471 (Bacterial Reverse Mutation Assay) with modifications

Results: negative / positive

Method: OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)

Results: negative

Method: OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Results: negative / positive

Literature information: REACH Dossier

In vivo mutagenicity/genotoxicity

Method: OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Results: negative ; Literature information: REACH Dossier

Reproductive toxicity

Method: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)

Exposure time: 28d; Species: Rat

Results: NOAEL = > 2000 mg/kg(bw)/day; Literature information: REACH Dossier

Developmental toxicity/teratogenicity:

Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study)

Exposure time: 28d; Species: Rat

Results: NOAEL = > 2000 mg/kg(bw)/day; Literature information: REACH Dossier

STOT-single exposure

Based on available data, the classification criteria are not met.

Product Name: Hansaflex Öl HVLPD 46
Revision: 01.07.2025

STOT-repeated exposure

Based on available data, the classification criteria are not met.
Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified:
Subchronic oral toxicity:
Exposure time: 90d
Species: Sprague-Dawley Rat.
Method: OECD Guideline 408
Result: LOAEL = 125 mg/kg
Literature information: REACH Dossier

Subacute inhalative toxicity :
Exposure time: 28d
Species: Sprague-Dawley Rat.
Result: NOAEC > 980 mg/m³
Literature information: REACH Dossier

Subacute dermal toxicity :
Exposure time: 28d
Species: Rabbit
Method: OECD Guideline 410
Result: NOAEL 1000 mg/kg
Literature information: REACH Dossier

Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified:
Subacute inhalative toxicity : Method: -; Exposure time: 28d; Species: Rat; Results: NOAEL > 980 mg/m³;
Literature information: J Appl Toxicol, Vol 11(4), pp 297-302; Subacute dermal toxicity: Method: OECD
Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study); Exposure time: 28d; Species: Rabbit;
Results: NOAEL 1000 mg/kg(bw)/day; Literature information: REACH Dossier; Subchronic oral toxicity:
Method: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents); Species: Rat; Results:
NOAEL = 125 mg/kg; Literature information: REACH Dossier

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance (> 0,1 %) that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other information

Frequent contact specially if dried out may cause skin and eye irritations.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

Product Name: Hansaflex Öl HVLPD 46
Revision: 01.07.2025

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LC50 >100 mg/l	96 h	Pimephales promelas	ECHA Dossier	
	Acute algae toxicity	ErC50 >100 mg/l	72 h	Pseudokirchnerella subcapitata	ECHA Dossier	
	Acute crustacea toxicity	EC50 >10000 mg/l	48 h	Daphnia magna	ECHA Dossier	
	Crustacea toxicity	NOEC 10 mg/l	21 d	Daphnia magna	ECHA Dossier	
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LC50 LL50 > 100 mg/l	96 h	Pimephales promelas (fathead minnow)	ECHA Dossier	OECD Guideline 203
	Acute crustacea toxicity	EC50 EL50 >10000 mg/l	48 h	Daphnia magna (Big water flea)	ECHA Dossier	OECD Guideline 202
	Algae toxicity	NOEC NOEL > 100 mg/l	3 d	Pseudokirchneriella subcapitata	ECHA Dossier	
	Crustacea toxicity	NOEC NOEL > 10 mg/l	21 d	Daphnia magna (Big water flea)	ECHA Dossier	OECD Guideline 211

12.2. Persistence and degradability

The product is slightly soluble in water. It can be largely eliminated from the water by abiotic processes, e.g. mechanical separation.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil - unspecified			
	OECD 301B / ISO 9439 / EEC 92/69 annex V, C.4-C	2-4%	28	ECHA Dossier
	Not easily bio-degradable (according to OECD-criteria).			
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified			
	OECD Guideline 301 F	31%	28	ECHA Dossier
	Not easily bio-degradable (according to OECD-criteria).			

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified	> 3,5

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. The aforementioned statement applies to substances contained in the product with a minimum content of 0.1%.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The aforementioned statement applies to substances contained in the product with a minimum content of 0.1%.

12.7. Other adverse effects

No information available.

Product Name: Hansaflex Öl HVLPD 46
Revision: 01.07.2025

Further information

Ozone depletion potential (ODP): No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Informations for safe handling see chapter 7.

Informations for personal protective equipment see chapter 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Product Name: Hansaflex Öl HVLPD 46
Revision: 01.07.2025

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 75

Directive 2010/75/EU on industrial emissions: No information available.

Directive 2004/42/EC on VOC in paints and varnishes: No information available.

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (amended by Regulation (EU) No 2020/878)

This mixture is classified as not hazardous according to Regulation (EC) 1272/2008 [CLP].

REACH 1907/2006 Appendix XVII, No (mixture): not relevant

Observe in addition any national regulations!

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

Additional information

Regulation (EU) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals: not relevant

15.2 Chemical Safety Assessment
not applicable.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 12,15,16.

Rev.: 1,0 - 07.05.2015

Rev.: 1,1 - 22.01.2016

Rev.: 1,11 - 18.04.2016

Rev.: 1,2 - 31.01.2017

Rev.: 2,0 - 18.01.2018

Rev.: 3,0 - 25.01.2019

Rev.: 4,0 - 15.01.2020; Changes in chapter: 1.2, 8.1, 8.2, 10.3, 15.1, 16

Rev.: 4,1 - 23.07.2020; Changes in chapter: 9.1, 16

Rev.: 5,0 - 02.07.2021; Changes in chapter: 3.2, 6.1, 6.3, 11.2, 12.6, 12.7, 15.1, 16

Rev.: 6,0 - 29.07.2022; Changes in chapter: 2.3, 8.2, 12.5, 12.6, 16

Rev.: 6,1 - 22.11.2022, Changes in chapter: 3.2, 8.1, 11.1, 12.1, 12.2, 16

Rev.: 7,0 - 14.11.2023, Changes in chapter: 8.1, 9.1, 11.2, 12.1, 12.7, 16

Rev.: 8,0 - 05.11.2024, Changes in chapter: 12.1, 16

Product Name: Hansaflex Öl HVLPD 46
Revision: 01.07.2025

Abbreviations and acronyms

Asp. Tox. 1: Aspiration hazard, hazard category 1
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
CAS: Chemical Abstracts Service
CLP: Classification, Labelling and Packaging of substances and mixtures
d: day(s)
DNEL: Derived No Effect Level
IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER
EINECS: European INventory of Existing Commercial chemical Substances
ELINCS: European List of Notified Chemical Substances
ECHA: European Chemicals Agency
EWC: European Waste Catalogue
IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)
h: hour
LOAEL: Lowest observed adverse effect level
LOAEC: Lowest observed adverse effect concentration
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
NOAEL: No observed adverse effect level
NOAEC: No observed adverse effect concentration
NLP: No-Longer Polymers
NTP: National Toxicology Program
N/A: not applicable
OECD: Organisation for Economic Co-operation and Development
PNEC: predicted no effect concentration
PBT: Persistent bioaccumulative toxic
PMT: Persistent, mobile and toxic
REACH: Registration, Evaluation, Authorisation of Chemicals
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
SVHC: substance of very high concern
TRGS: Technische Regeln für Gefahrstoffe
UN: United Nations
TSCA: Toxic Substances Control Act
vPvM: very persistent and very mobile
vPvB: very persistent and very bioaccumulative
VOC: Volatile Organic Compounds
WGK: Water Hazard Class (Germany)

Key literature references and sources for data

<https://echa.europa.eu/>
<https://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index.jsp>
<https://cfpub.epa.gov/ecotox/search.cfm>
<http://www.inchem.org/#/search>
<https://pubchem.ncbi.nlm.nih.gov/>
<http://ccinfoweb.ccohs.ca/rtecs/search.html>
<https://webrigoletto.uba.de/rigoletto/>

Relevant H and EUH statements (number and full text)

Product Name: Hansaflex Öl HVLPD 46
Revision: 01.07.2025

H304 May be fatal if swallowed and enters airways.
EUH210 Safety data sheet available on request.

Further Information

Classification according to Regulation (EC) No 1272/2008 [CLP] - Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)